

Excel Category 6 (UTP) Low Profile Toolless Jack - Black

100-208-BK



Features

- Nordic market specific
- High quality polymer housing
- Low profile design - just 28mm overall depth
- Toolless termination design
- Supports Gigabit Ethernet application
- Delta 3rd party verified

Product Overview

The Excel Category 6 Low Profile Unscreened Keystone Jack is a reduced size toolless termination RJ45 socket. The reduced size allows for multiple cable entry directions to be accommodated when this jack is mounted in a standard depth back box. This permits many mounting options including flush shutters at the outlet as well as more common angled shutter used with keystone jacks.

A choice of compatible Patch Panel frames with either 16 or 24 port density in both black and chrome are available for this Low Profile Jack. The low profile design allows this jack to fit in the Excel 0.5U 24 Port Patch Panel resulting in a maximum port density of 48 per 1U. The socket itself is housed in a high quality fire retardant plastic cast housing, which opens at the rear in a butterfly manner to reveal the IDC termination points. Once the pairs are arranged in the cable management cap and trimmed it is a simple case of closing the 'butterfly' together to complete the termination.

Third party verification by Delta assures this high performance jack exceeds the requirements of the ISO, EN & TIA component standards.

Features	
1: Model	Jack
2: Type of connector	RJ45 8(8)
3: Shielded	no
4: Category	6
5: Special tool necessary	no
6: Suitable for round cable	yes
7: Suitable for flat cable	no
8: Suitable for solid core	yes
9: Colour	Black
10: AWG-range	22...26