

DIGITUS Professional CAT 6A Keystone Module, unshielded

DN-93606 4016032366317



DIGITUS CAT 6A Keystone Jack, unshielded
500 MHz acc. ISO/IEC 11801:2002 AM2:2009/09, tool free connection

The Keystone Module "DN-93606" from DIGITUS® is unshielded and provides with tool free installation best performance and link quality for your network. The compact design allows the installation of 24 pieces in a row of 483 mm (19") 1U Panels. It is conform to Category 6A / 10GBase-T Channel, ANSI/EIA/TIA 568C.2.1:2002, ISO/IEC 11801:2002.



- 1 Transmission properties: Category 6A, Class EA
- 1 Area of application: Up to 500 MHz, 10GBase-T
- 1 Norms: ISO/IEC 11801 2nd Ed., EN 50173-1, EIA/TIA 568-C, 802.3af, 802.3at PoE+
- 1 General properties:
- 1 Suitable for 483 mm (19") cabinet mounting
- 1 RJ45 female, 8P8C
- 1 Cable installation via LSA strips, color coded according to EIA/TIA 568 A & B
- 1 Cable fixing with cable tie
- 1 Tool-free installation
- 1 Technical properties:
- 1 RJ45 female material: ABS UL 94V-0
- 1 RJ45 female contact: Tinned phosphor bronze, 0.5 µ gold-plated contact
- 1 LSA termination clamp: Krone LSA+, UL 94V-2, zinc plated phosphor bronze
- 1 Conductor plate: FR4, UL 94V-0
- 1 Physical properties:
- 1 Insertion force: 30N max. (IEC 60603-7-5)
- 1 Retention strength: 7.7 kg between jack and plug
- 1 Operation temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)
- 1 Mating cycles female: > 750 acc. to ISO/IEC 11801, IEC 60603-7-5
- 1 Clamp: > 200 acc. to ISO/IEC 11801, IEC 60603-7-5
- 1 IDC wire size: 22 – 26 AWG solid and stranded conductor
- 1 Insulation resistance: > 500 MOhm
- 1 Contact resistance: < 20 MilliOhm
- 1 Dielectric strength: 1000 VDC (Contact/Contact), 1500 VDC (Contact/Ground)

DIGITUS Professional CAT 6A Keystone Module, unshielded

DN-93606 4016032366317



→ Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	250	3,80	53,00	33,00	22,00	38478,00
Packaging Unit Inside	25	0,38	10,00	20,00	14,00	2800,00
Packaging Unit Single	1	0,02	2,00	8,00	10,00	160,00
Net single without Packaging	1	0,02	2,00	8,00	10,00	160,00

→ Packaging type

